

# C2SAT Ku100MIL

## DESIGNED FOR NAVY VESSELS

The C2SAT Ku100MIL is a high performance stabilized VSAT antenna designed to meet US Military standards for vessels participating in sea warfare and defence. The antenna is easy to install, light and small - yet reliable and providing superior radio performance to support mission critical applications used on a modern battle ship.

- Weight < 150 Kg
- Height: 1.35 m
- Diameter: 1.45 m
- Antenna completely assembled, balanced and tested at factory to support fast deployment

## 4-AXES TECHNOLOGY

C2SAT provides stabilized VSAT antennas built on a unique and proven 4-axes technology. The design enables shorter geometric path and less rotation torque for each axis, extending the life of the mechanical parts of the antenna as the system is subjected to less stress than a 3-axes system. The fourth axis also solves problems related to the zenith paradox occurring in a wide belt around the equator at high reflector elevations.

## SUPERIOR REFLECTOR SOLUTION

The antenna design is of Prime Focus type and the reflector is made of carbon fibre, standard for C2SAT antennas. The RF equipment is therefore light and easy to manoeuvre for the stabilizing platform, which facilitates fast and precise movements. The antenna complies with the requirements of Eutelsat and provides several technical advantages, such as;

- High gain
- Low side lobes
- High cross-pol discrimination
- Up to 50W BUC
- EIRP (with 50W BUC) 59 dBW
- Resistant to disturbance from other radio sources



## FAST & ROBUST SYSTEM

The antenna system is fast due to the gimbal design with AC motors on each axis and the gradient satellite tracking method on all 4 axes. The antenna locks on the satellite within 8 seconds, starting from its parking position. Robustness is built into the system, partly because of the solid rig construction, but also because the 4-axis gimbal design facilitates less weight to move and a minimum of movement for each axis - all of the time.

## REMOTE OPERATION AND MAINTENANCE

C2SAT antennas are generally designed for remote Operation and Maintenance. The functionality includes;

- Real time supervision with access to performance statistics
- Remote management using SNMP
- Remote access control using SSH
- Remote access to configuration and control tools via web browser
- Remote uploading of firmware to the system

## COMPLIANCE TO STANDARDS

C2SAT Ku100MIL meets military standard specifications concerning vibration, shock, and EMC according to MIL STD 810G and MIL STD 461F.

# C2SAT Ku100MIL

FEATURES	SPECIFICATION DATA
Stabilisation Type	4-axes gimbals. AC servo low inertia belt drive.
Antenna Type	Prime Focus
Reflector Diameter	1 m (39")
Radome Size	H: 1.35 m (53") D: 1.45 m (57")
Weight including Radome	150 kg (330 lbs)
Frequency	Rx: 10.95 – 12.75 GHz / Tx: 13.75 – 14.5 GHz
Antenna Gain	Rx: 40.0 dBi / Tx: 42.0 dBi
Reflector Material	Carbon Fibre
Side lobe Envelope	33–25 log (Θ)
Cross Polarization	Tx: > 35 dB within 1dB cone
Signal Polarization	Linear Cross-pol
G/T (@ 20° elevation, typical)	18.5 dB/K @ 12.2 GHz
Maximum BUC Power	50W internal BUC
Antenna Movement, azimuth	Continuous, unlimited (slip ring)
Antenna Movement, Elevation	0 – 120°
Antenna Movement, Cross Level	± 30°
Antenna Movement, Polarisation	± 120°
Ship Motion	± 30° per 4s in pitch, roll and yaw
Heave	+/- 5m @3s
Pointing accuracy	0.1° RMS
GPS Antenna	Built in
Radar Rejection	>80 dB @ 9.6 GHz
Radome Material	Polyester laminate with Trident foam core
Compass Interface	NMEA 0183
Nominal Voltage:	115VAC @ 60 Hz or 220 – 230VAC @ 50/60 Hz
Operating Temperature	-20 – 55 °C
Humidity	97% @ 30 °C
Vibration Operating	MIL-STD-810G, Metod 528, Table 528.III
Shock Operating	20 g, half-sine 11 ms, MIL-STD-810G, Method 516.6
Shock Non-Operating	Transverse / Longitudinal: 20 g 20 ms; 40 g 6 ms Vertical: 15 g 20 ms; 30 g 6 ms
EMC	MIL STD 461F



**Robust Antennas For The Most Demanding Customers**

C2SAT, ISAFJORDSGATAN 32B, SE-164 40 KISTA, SWEDEN, + 46 8 705 95 00.

C2SAT, 79 LOYANG WAY, SINGAPORE 508765, +65 6225 8826.

sales@c2sat.se, [www.c2sat.com](http://www.c2sat.com)